



GOLDMUND
SWISS MADE

HOME CINEMA SPEAKER

LOGOS WALL MK2

EXTREME MULTICHANNEL

The Logos Wall epitomizes unparalleled auditory excellence, harnessing the pinnacle of home cinema sound technologies: Goldmund's Telos, Proteus HT, Proteus LS, and Leonardo©, ensuring the most precise sound reproduction imaginable.



GOLDMUND
SWISS MADE



HOME CINEMA SPEAKER

LOGOS WALL MK2

FREQUENCY RESPONSE

45 Hz – 25 KHz (-6 dB)

AMPLIFIER

Built-in 2 x 175 W Telos amplifier for tweeter & medium per unit

DRIVER

1 x soft dome tweeter

1 x 6.5" medium

THE HEART OF HOME CINEMA

When integrated with our acoustic processors, it becomes a cornerstone of the Extreme Multichannel setup that Goldmund advocates for any discerning home cinema enthusiast.

BASS LOAD

Vent loading

INPUTS

1 x digital S/PDIF

OUTPUT

1 x digital S/PDIF.

VOLTAGE

Nominal range: 115 V or 230 V (+/-15 %)

Fuses: 8 A slow-blow type for 115 V & 230 V

RATED POWER CONSUMPTION

240 W per unit

SIZE & WEIGHT

32 W x 13 D x 66.5 L (cm) – cabinet.

39 W x 1 D x 68.5 L (cm) – front panel.

30 kg.