



WIRELESS HUB

MIMESIS 11

WITH PURPOSE

In Greek, Telos means purpose or goal, and the Telos 440 power amplifier is designed to fulfill its purpose by delivering exceptional power amplification. Its mission is to elevate the input signal to remarkable levels, effortlessly driving any passive speaker.



INPUTS

3 digital inputs

- 1 x USB device: Audio Class 2.0
 - no driver required on Mac OS X as of v.10.6.4 nor on Linux; driver required only for Windows (contact your Goldmund representative)
 - Sample rate up to 384 kHz/Bit depth up to 32
 - DSD64, DSD128 over PCM capabilities
- 1 x Toslink Optical (up to 384kHz/24bits)
- 1 x Digital S/PDIF coaxial RCA 75 Ohms (up to 384kHz/24bits)

1 analog input

- RCA 2-channel

OUTPUTS

- 4 parallel Digital RCA S/PDIF 2-channel outputs
- 1 Wireless outputs 4 channels max

FRONT PANEL CONTROLS

- 2 knobs for input selection and volume control
- Numeric displays for input selection
- Numeric displays for volume
- Power and lock LED

POWER

- Nominal line voltage: 115 V or 230 V (switchable)
- Input voltage range: +/- 10 %
- Rated power consumption: 11 W
- 1,6 A delayed fuse
- ON/OFF power switch key
- Main voltage selector

SIZE & WEIGHT

- 44 W x 14 H x 37 D (cm)
- 17.3 W x 5.5 H x 14.2 D (inch)
- 8 kg

COLORS

- Grey