

ACTIVE STEREO SPEAKER

0

SATYA

HEIGHT OF PRECISION

Satya refers to 'truth' in Sanskrit, a coherence with reality in one's thoughts, words and actions. These principles of coherence characterise Satya amplified loudspeakers in the technology used and the performance delivered.

WWW.GOLDMUND.COM





ACTIVE STEREO SPEAKER

SATYA

DRIVERS

PRECISE

The modeling calculates the loudspeaker system in impedance, volume velocity, membrane displacement, and sound pressure anywhere in space, amplitude, phase, and group delay.

Each speaker pair is securely packaged in two custom flight cases, specifically designed to ensure optimal protection during storage and transport.

SPECIFICATIONS PER UNIT

1 x soft dome tweeter	
1 x 7" medium	
1 x 12" woofer, selected for their high linear and dynamics	ity
FREQUENCY RESPONSE	
28 Hz (-6 dB) > 25 kHz	
BASS LOAD	
Vent loading	
VOLTAGE	

Nominal range: 115 V or 230 V (+/-15%)

AMPLIFIER (BUILT-IN TELOS)

Built-in 650 W Telos amplifier per unit
2 x 175 W for tweeter & medium
1 x 300 W for wooferr

INPUTS

1 x digital S/PDIF 1 x wireless audio

RATED POWER CONSUMPTION

480 W per unit

SIZE & WEIGHT

56 W x 123 H x 63 D (cm) 22.05 W x 48.43 H x 24.80 D (in) 140 Kg

FLIGHTCASE SIZE & WEIGHT

59 W x 140 H x 79 D (cm) 23.23 W x 55.12 H x 31.10 D (in) 177 Kg

COLOR

Matte Grey Enclosure | Black Grids Matte Black Enclosure | Black Grids